

# ENSTO

## PRODUCT SPECIFICATION

2020-02-24



6418677403538

Insulation piercing connector

SL11.118

|             |                                                                                                                                       |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Code        | SL11.118                                                                                                                              |
| GTIN        | 6418677403538                                                                                                                         |
| Name        | Insulation piercing connector<br>Al 10-95 mm <sup>2</sup> or Cu 1.5-70 mm <sup>2</sup>                                                |
| Description | Universal connector for all combinations of aluminium and copper main and branch connectors. SL11.118 is for PEX insulated conductor. |

Vendor



## Technical specification

### Others

ETIM Class: EC001062

### Features

Bolt: M8

### Dimensions

Branch conductor mm<sup>2</sup>: Al 10-95 / Cu 1.5-70

Conductor diameter: 3 ... 16 mm

Main conductor mm<sup>2</sup>: Al 10-95 / Cu 1.5-70

Weight: 0,12 kg

### Mechanical

Tightening torque Nm: 26 Nm

## ETIM 7

### Etim

Clamping channel opening branch conductor: Closed

Clamping channel opening main conductor: Closed

Material branch conductor: Aluminium/copper

Material main conductor: Aluminium/copper

|                                               |                                   |
|-----------------------------------------------|-----------------------------------|
| Nominal cross section branch conductor SE/RE: | 1,5 ... 95 mm <sup>2</sup>        |
| Nominal cross section branch conductor SM/RM: | 1,5 ... 95 mm <sup>2</sup>        |
| Nominal cross section main conductor SE:      | 1,5 ... 95 mm <sup>2</sup>        |
| Nominal cross section main conductor SM:      | 1,5 ... 95 mm <sup>2</sup>        |
| Surface protection:                           | Tinned                            |
| Terminal insulated:                           | True                              |
| Type of connection:                           | Insulation piercing connector IPC |

## Packaging

---

### Pallet package

|               |         |
|---------------|---------|
| Unit:         | PCE     |
| Package size: | 3150    |
| Depth:        | 1200 mm |
| Width:        | 800 mm  |
| Height:       | 1050 mm |

### Default package

|               |          |
|---------------|----------|
| Unit:         | PCE      |
| Package size: | 50       |
| Depth:        | 385 mm   |
| Width:        | 260 mm   |
| Height:       | 130 mm   |
| Volume:       | 13,013 l |