

ENSTO

PRODUCT SPECIFICATION

2020-02-24



6418677416194

IPC / Bare connector

SLIP22.127

Code SLIP22.127

GTIN 6418677416194

Name IPC / Bare connector
Main Al 25-95 or Cu 25-70 Branch Al 2.5-95
or Cu 1.5-70 mm²

Description SLIP22.127 is for all connections of
uninsulated aluminium and copper main
and insulated branch conductors up to
1000 VAC. Equipped with shear head
screw.

Vendor



Technical specification

Others

ETIM Class: EC001062

Certificates

Connector class: A2

Standards: EN 50483-4:2009

Features

Bolt: M8x50

Drawing markings

d1: 6.5-16.0

d2: 3.0-16.0

Mechanical

Tightening torque Nm: 18,5 Nm

Electrical values

Highest system voltage: 1 kV

ETIM 7

Etim

Clamping channel opening branch conductor:	Closed
Clamping channel opening main conductor:	Closed
Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	2,5 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	2,5 ... 95 mm ²
Nominal cross section main conductor SE:	25 ... 95 mm ²
Nominal cross section main conductor SM:	25 ... 95 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	PCE
Package size:	2700
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm

Default package

Unit:	PCE
Package size:	50
Depth:	385 mm
Width:	260 mm
Height:	165 mm
Volume:	16,5165 l