



Moduł przyłączeniowy, 1.5-16mm², 3b, 20mm

Typ
Catalog No.

BBA-TP3/16
107205

Program dostaw

Asortyment			System 60-mm
Funkcja podstawowa			Technika przyłączy i połączeń
Grupa asortymentowa			Adaptery przyłączeniowe
Tworzywo			Bez silikonu, bez chloru
Samogaśnienie			zgodnie z UL 94
Odporność na wyładowania pełzne			CTI 200
Odporność temperaturowa			do 120°C
Sposób podłączenia			Technika zacisków sprężynowych
Szerokość		mm	20
Bieguny			3
Znamionowy prąd pracy	I _e	A	80
Przewód			1.5 - 16 mm ² AWG 16 - AWG 6.  
Cu factor		kg	0,00
Stosowane do			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
Stosowane do			Double T profile

Wskazówki

 round conductor, solid

 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Sector conductor, solid

Sector conductor, stranded

CU band

 CU busbar

Aprobaty

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC

Wymiary

