

Zacisk szczękowy, 1000mm² do 30x10 i profilu T
Typ
Catalog No.
AKS1000
107208

Program dostaw

Asortyment			System 60-mm System 185-mm
Funkcja podstawowa			Technika przyłączy i połączeń
Grupa asortymentowa			Zaciski szczękowe
Opis			Bezdotykowa technika połączeń na szynach zbiorczych Stykowanie przewodu z szyną zbiorczą odbywa się poprzez blok stykowy
Terminal area W x H		mm	55 x 28
Szerokość		mm	72
Znamionowy prąd pracy	I _e	A	1600
Przewód			do # (2 x) 10 x 50 x 1 mm do ■ (2x) 50 x 10 mm
Cu factor		kg	0,20
Stosowane do			20 x 5/10 25 x 5/10 30 x 5/10
Stosowane do			Double T profile
Wskazówki ☐ round conductor, solid ☒ Flexible, round conductor with correctly crimped ferrule Round conductor, stranded ☐ Section conductor, solid Sector conductor, stranded # CU band ■ CU busbar			

Aprobaty

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

