

Product data sheet

Specifications



PLAIN DOOR+FRAME W600 19M PRISMA G IP55

LVS08325

Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Door
Range compatibility	PrismaSeT (PrismaSeT G) enclosure
Provided equipment	door handle keylock (key 405) other keylock and insert to be ordered separately 2 hinge
Type of door	Plain
IP degree of protection	IP55

Complementary

Installation description	Wall-mounted enclosure - width 600 mm Extension enclosure - width 600 mm
Door opening side	Reversible
Number of locks	3
Door opening angle	180 °
Number of vertical modules [50 mm]	19
Enclosure material	Treated sheet steel
Quantity per set	Set of 1
Height	1050 mm
Width	600 mm
Depth	26 mm
Net weight	16.2 kg
Surface finish	Matt Textured
Colour	White (RAL 9003)

Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-2 IEC 61439-1

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
----------------------	----------------------------------------------------------------------


Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	60.5 cm
Package 1 Length	104.0 cm
Package 1 Weight	15.957 kg
Unit Type of Package 2	P12
Number of Units in Package 2	10
Package 2 Height	86.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	172.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Dimensions



- All dimensions are approximate and are in mm.
- Also see technical documentation.

Recommended replacement(s)