

Language

Page

Revision

Creation date

2024-04-05

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS																		
Motor type: 1AV3112A SIMOTICS GP - 112 M - IM B5 - 2p															•			
Client ord	der no.				lte	Item-No.						Offer no.						
Order no.					Co	Consignment no. Project												
Remarks																		
Electri	cal dat	:a									Saf -/-	e Area						
U	Δ/Υ	f	Р	Р	1	n	М		η 3)			cosφ ³⁾		I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
		=0					L duty (S1)	1						١				
400 690	Δ Υ	50 50	4.00	-/-	7.40 4.25	2945 2945	13.0	88.1	88.8	87.9 87.9	0.89	0.84	0.76	9.1 9.1	2.6	3.6	IE3	
460	Δ	60	4.55	-/-	7.30	3545	12.3	88.5	88.5	87.2	0.89	0.85	0.78	9.7	2.7	3.8	IE3	
460	Δ	60	4.00	-/-	6.40	3550	10.8	88.5	88.4	86.7	0.88	0.83	0.75	10.9	3.1	4.3	IE3	
IM B5 / IM 3001 FS 112 M						IP55	UKCA		IEC/EN 60034 IEC			C, DIN, ISO, VDE, EN						
		Enviror	nmental c	onditions :	-20 °C - +4	10 °C / 10	00 m	Locked rotor time					(hot / cold) : 7 s 10.2 s					
Mecha	nical d	lata																
Sound	level (SI	PL / SWL)) at 50Hz 60)Hz 73	/ 81 dB(A) ²⁾	3) 80 /	88 dB(A) ^{2) 3)}	Vibr	Vibration severity grade					А				
Moment of inertia						0079 kg m²		Thermal class					F					
Bearing DE NDE 6206 2Z 0						62	206 2Z C3	Duty type					\$1					
bearing lifetime							Direction of rotation				bidirectional							
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾					40000 h 32000 h				Frame material				aluminum					
Regreasing device					٧	Without			Net weight of the motor (IM B3)				32 kg					
Grease nipple						-/-			Coating (paint finish)				Standard paint finish C2					
Type of bearing					Preload	Preloaded bearing DE			Color, paint shade				RAL7030					
Conde	nsate dr	ainage h	noles		Without				Motor protection					(A) without (Standard)				
External earthing terminal					Without				Method of cooling					IC411 - self ventilated, surface cooled				
Termir	nal box	(
Terminal box position					top				Max. cross-sectional area				4 mm²					
Material of terminal box					Aluminium				Cable diameter from to				11 mm - 21 mm					
Type of terminal box					TB1 F00				Cable entry				2xM32x1,5					
Contact screw thread					M4				Cable gland				2 plugs					
$M_A/M_N = lo$ $M_K/M_N = bi$	cked rotor i reak down t	torque / non	que nominal minal torque	2)	L _{10mh} according to at rated power I	at full load						only for DOL						
				editing of this doc gistration of a util			contents and com served.	munication t	hereof to oth	ers without ex	press autho	orization are p	rohibited. Of	tenders will	be held liabl	e for paymer	nt of	
Responsible department Technical reference					erence	Created by					al data are subject to change! There may be ancies between calculated and rating plate				Link documents			
IN LVM				Dogument	20	SPC		created a	utomatic	ally value		mont state						
SIEMENS				Document type Technical data sheet								Document status Released						
			Document title							+	Document number							
				1LE1003-1BA23-4FA4									240405-144259					

© Innomotics 2024

Restricted