SIEMENS

Data sheet

6GK1901-1BB30-0AA0

product type designation product description



IE FC RJ45 Plug 145 (2x2) RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 145 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP cable 2x 2; 145° cable outlet 1 pack = 1 unit.

suitability for use

For connection to IE FC TP cables 2x2, suitable for fast assembly with the FastConnect system

	FastConnect system
transfer rate	
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s
interfaces	
number of electrical connections	
 for Industrial Ethernet FC TP cables 	4
 for network components or terminal equipment 	1
type of electrical connection	
 for Industrial Ethernet FC TP cables 	integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22
 for network components or terminal equipment 	RJ45 connector
type of electrical connection / FastConnect	Yes
mechanical data	
material / of the enclosure	metal
number of reuses	10
locking mechanism design	other
design, dimensions and weights	
type of cable outlet	145° cable outlet
width	13.9 mm
height	16 mm
depth	55.6 mm
net weight	35 g
connectable cable cross-section	6.5 6.5 mm
connectable conductor cross-section	0.33 mm ²
ambient conditions	
ambient temperature	
during operation	-40 +85 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
product features, product functions, product components / general	
product feature	
PoE capability	Yes
PoE+capability	Yes
silicon-free	Yes

product component		
strain relief	Yes	
standards, specifications, approvals		
certificate of suitability		
RoHS conformity	Yes	
• UL approval	Yes	
cULus approval	Yes	
 railway application in accordance with EN 50155 	No	
standard for structured cabling	Cat5	
standards, specifications, approvals / Environmental Product Declaration		
Environmental Product Declaration	Yes	
Global Warming Potential [CO2 eq]		
• total	0.277 kg	
 during manufacturing 	0.263 kg	
during operation	0.0086 kg	
after end of life	0.0062 kg	
further information / internet links		
internet link		
to website: Image database	https://www.automation.siemens.com/bilddb	
to website: Industry Online Support	https://support.industry.siemens.com	
security information		
Approvals / Certificates General Product Approval	that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)	
ERE Manufacturer Declara- Declaration form	nity un ate	
Marine / Shipping	Environment Industrial Commu- nication	
LIRS REMARK	Confirmation PROFINET	
last modified:	3/23/2024 🖸	