



Product Service

# Attestation of Compliance

No. E8N 13 12 80962 019

**Holder of Certificate:** **ABB Genway Xiamen Electrical Equipment Co., Ltd.**Room 501-1, No.12-14  
3rd Chuang Xin Road, Torch High Technology Development Zone  
361000 Xiamen S.E.Z, Fujian Province  
PEOPLE'S REPUBLIC OF CHINA**Name of Object:** **Access-Control System (Door Entry System)****Model(s):** **ABB-Welcome M****Description of Object:**Ratings:  
M2300Input: 100-240 V a.c., 50/60 Hz, 1.0 A;  
output: 28.0 V d.c., 1.2 A

M2301

Input: 100-240 V a.c., 50/60 Hz, 0.6 A;  
output: 28.0 V d.c., 0.65 A

See page 2-3 for more details

**Tested according to:**EN 61000-6-1:2007  
EN 61000-6-3/A1:2011  
EN 61000-3-2/A2:2009  
EN 61000-3-3:2008

This Attestation of Compliance is issued according to the Directive 2004/108/EC relating to electromagnetic compatibility on a voluntary basis. It confirms that the listed apparatus complies with all essential requirements of the EMC directive and applies only to the sample and its technical documentation submitted to TÜV SÜD Product Service GmbH for testing and certification. See also notes overleaf.

**Test report no.:** 64760130269401**Date,** 2013-12-23

( Tony Liu )



After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant directives have to be observed.

Page 1 of 3



Product Service

# Attestation of Compliance

No. E8N 13 12 80962 019

Part No.	Model No.	Technical data	Remark
System controller	M2300	Input: 100-240 V a.c., 50/60 Hz, 1.0 A; output: 28.0 V d.c., 1.2 A	
Min-system controller	M2301	Input: 100-240 V a.c., 50/60 Hz, 0.6 A; output: 28.0 V d.c., 0.65 A	
Camera module	M251021C	Input: 20-30 V d.c., 3W	
Audio module	M251021A-	Input: 20-30 V d.c., 4W	The "." in the model No. means the product color: A means aluminum alloy color; W means white; B means black.
Audio module, 1/2 pushbuttons	M251022A-	Input: 20-30 V d.c., 4W	
Audio module, 2/4 pushbuttons	M251023A-	Input: 20-30 V d.c., 4W	
Audio module with speech synthesis	M251024A-	Input: 20-30 V d.c., 4W	
3/6 pushbuttons module	M251021P3	Input: 20-30 V d.c., 0.25W	
4/8 pushbuttons module	M251021P4	Input: 20-30 V d.c., 0.25W	
Nameplate module	51021DN	Input: 20-30 V d.c., 0.25W	
Audio handset indoor station, 3 buttons	M22002-	Input: 20-30 V d.c., 1.5W	The "." in the model No. means the product color: A means aluminum alloy color; W means white; B means black.
Audio handset indoor station with induction loop	M22003-	Input: 20-30 V d.c., 1.5W	
Audio handset indoor station, 6 buttons	M22001-	Input: 20-30 V d.c., 1.5W	
4.3" B/W video handset indoor station	M22301-	Input: 20-30 V d.c., 4W	
4.3" Colour video handset indoor station	M22302-	Input: 20-30 V d.c., 4W	
4.3" Colour video handset indoor station with induction loop	M22303-	Input: 20-30 V d.c., 4W	
4.3" Video hands-free indoor station	M22311-	Input: 20-30 V d.c., 4W	
4.3" Video hands-free indoor station with induction loop	M22313-	Input: 20-30 V d.c., 5W	
Gateway	M2302	Input: 20-30 V d.c., 1.5W	
Guard unit	M2303	Input: 20-30 V d.c., 4W	
Video distributor	M2304	Input: 20-30 V d.c., 0.25W	
Switch actuator	M2305	Input: 20-30 V d.c., 1.5W	
Outdoor video distributor	83325/2-5..	Input: 20-30 V d.c., 0.25W	

Page 2 of 3





Product Service

# Attestation of Compliance

No. E8N 13 12 80962 019

Audio outdoor station, 1/2 pushbuttons (the product contain one audio module, 1/2 pushbuttons and one panel)	M21021P1-.	Input: 20-30 V d.c., 4W	The "." in the model No. means the product color: A means aluminum alloy color; W means white; B means black.
Video outdoor station, 1/2 pushbuttons (the product contain one camera module and one audio module, 1/2 pushbuttons and one panel)	M21351P1-.	Input: 20-30 V d.c., 7W	
Keypad module	M251021K-. M251022K-.	Input: 20-30 V d.c., 0.5W	
7" Video hands-free indoor station	M22331-.	Input: 20-30 V d.c., 6.4W	
Video outdoor station with keypad, with ID card reader	M21351K-.	Input: 20-30 V d.c., 12W	
Video outdoor station with keypad, with IC card reader	M21352K-.	Input: 20-30 V d.c., 12W	
Display module (Display module with ID card reader or Display module with IC card reader)	M251021CR M251022CR	Input: 20-30 V d.c., 3.9W	

Test report no.: 64760130269401

Date, 2013-12-23