



zacisk przyłączeniowy przepust kabla z lewej strony 690 V AC, DC 1000 V, 80 A
IP20

Wersja	
Nazwa markowa produktu	SETRON
oznaczenie produktu	Systemy szyn zbiorczych
wykonanie produktu	Akcesoria
Napięcie zasilania	
napięcie robocze przy AC wartość znamionowa	690 V
Połączenia	
moment dokręcenia	
• minimalny	1 N·m
• maksymalny	2 N·m
rodzaj przekrojów poprzecznych możliwych do podłączenia przewodów dla przewodów Cu wielożyłowy	6-25 mm ²
Konstrukcja mechaniczna	
wysokość	17,7 mm
szerokość	17,5 mm
głębokość	13 mm
długość	26,5 mm
masa netto	13,5 g
Zezwolenia Certyfikaty	
General Product Approval	other



[Confirmation](#)

[Miscellaneous](#)



[Miscellaneous](#)

other	Environment
Confirmation	Environmental Con- firmations
	Environmental Con- firmations

Więcej informacji
Informacje dotyczące opakowania Informacje dotyczące opakowania Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768-4 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/pl/ps/5ST3768-4

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768-4

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

Ostatnia zmiana:

12.03.2024 

