

## Assembly adapters - PTFIX 1,5-RZF - 1050613

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Adapter for direct mounting



### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 20 pc                                                                                                   |
| Minimum order quantity | 20 pc                                                                                                   |
| GTIN                   | <br>4 055626 665290 |
| GTIN                   | 4055626665290                                                                                           |

### Technical data

#### General

|                                          |                                                                        |
|------------------------------------------|------------------------------------------------------------------------|
| Color                                    | gray                                                                   |
| Ambient temperature (operation)          | -60 °C ... 85 °C                                                       |
| Ambient temperature (storage/transport)  | -25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C) |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                          |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                        |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                        |

#### Dimensions

|        |         |
|--------|---------|
| Width  | 28 mm   |
| Length | 21.6 mm |
| Height | 9.8 mm  |

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27370419 |
| eCl@ss 11.0   | 27370419 |

## Assembly adapters - PTFIX 1,5-RZF - 1050613

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27180401 |
| eCl@ss 4.1 | 27180401 |
| eCl@ss 5.0 | 27180506 |
| eCl@ss 5.1 | 27370400 |
| eCl@ss 6.0 | 27370400 |
| eCl@ss 7.0 | 27370419 |
| eCl@ss 8.0 | 27370419 |
| eCl@ss 9.0 | 27370419 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001031 |
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC001031 |
| ETIM 5.0 | EC001024 |
| ETIM 6.0 | EC001024 |
| ETIM 7.0 | EC001024 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |
| UNSPSC 18.0   | 39121708 |
| UNSPSC 19.0   | 39121708 |
| UNSPSC 20.0   | 39121708 |
| UNSPSC 21.0   | 39121708 |

### Approvals

#### Approvals

---

##### Approvals

EAC / CSA / cUL Recognized / UL Recognized / cULus Recognized

---

##### Ex Approvals

---

#### Approval details

## Assembly adapters - PTFIX 1,5-RZF - 1050613

### Approvals

|     |                                                                                   |                          |
|-----|-----------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.AI30.B.01102 |
|-----|-----------------------------------------------------------------------------------|--------------------------|

|                    |                                                                                   |                                                                                                                                         |       |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|                    | B                                                                                 | C                                                                                                                                       | D     |
| Nominal voltage UN | 300 V                                                                             | 150 V                                                                                                                                   | 300 V |
| Nominal current IN | 20 A                                                                              | 20 A                                                                                                                                    | 10 A  |
| mm²/AWG/kcmil      | 26-12                                                                             | 26-12                                                                                                                                   | 26-12 |

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| cUL Recognized     |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    | B                                                                                 | C                                                                                                                                                     | D            |
| Nominal voltage UN | 300 V                                                                             | 150 V                                                                                                                                                 | 300 V        |
| Nominal current IN | 15 A                                                                              | 15 A                                                                                                                                                  | 10 A         |
| mm²/AWG/kcmil      | 26-14                                                                             | 26-14                                                                                                                                                 | 26-14        |

|                    |                                                                                     |                                                                                                                                                       |              |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| UL Recognized      |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    | B                                                                                   | C                                                                                                                                                     | D            |
| Nominal voltage UN | 300 V                                                                               | 150 V                                                                                                                                                 | 300 V        |
| Nominal current IN | 20 A                                                                                | 20 A                                                                                                                                                  | 10 A         |
| mm²/AWG/kcmil      | 26-12                                                                               | 26-12                                                                                                                                                 | 26-12        |

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| cULus Recognized |  |
|------------------|-------------------------------------------------------------------------------------|