



OPASKI GT - naturalne

materiał: poliamid 6.6

temp. montażu: -10°C do +60°C

temp. pracy: -40°C do +85°C

wytrzymałość dielektryczna: 50kV/mm²

absorpcja wody: 2,5% (50% R.H., +23°C)

palność: UL-94 V2

tolerancja: ±5%



TYP	ROZMIAR [mm]	max/min ŚREDNICA [mm]	WYTRZYMAŁOŚĆ [kg]	OPAKOWANIE [szt]	
GT-100MCS	100x1,9	20/3	8	100	☐
GT-100MC	100x2,5	20/3	8	100	☐
GT-120MC	120x2,5	27/3	8	100	☐
GT-140MC	140x2,5	33/3	8	100	☐
GT-160MC	160x2,5	43/3	8	100	☐
GT-200MC	200x2,5	52/3	8	100	☐
GT-120IC	120x3,2	28/3	18	100	☐
GT-140IC	140x3,6	33/3	18	100	☐
GT-150IC	150x3,6	36/3	18	100	☐
GT-200IC	200x3,6	52/3	18	100	☐
GT-250IC	250x3,6	68/3	18	100	☐
GT-300IC	280x3,6	78/3	18	100	☐
GT-370IC	368x3,6	105/3	18	100	☐
GT-160STC	160x4,5	36/3	22	100	☐
GT-190STC	190x4,8	49/3	22	100	☐
GT-250STC	250x4,5	68/3	22	100	☐
GT-300STC	300x4,8	81/3	22	100	☐
GT-370STC	368x4,8	100/3	22	100	☐
GT-430STC	430x4,8	122/3	22	100	☐
GT-500STC	500x4,8	154/3	22	100	☐
GT-200HD	200x7,6	50/8	55	100	☐
GT-300HD	300x7,6	80/8	55	100	☐
GT-370HD	370x7,6	101/8	55	100	☐
GT-430HD	450x7,6	128/8	55	100	☐
GT-530HD	540x7,6	159/8	55	100	☐
GT-770HDL	780x8,8	227/8	80	100	☐
GT-830HDL	812x9,0	243/8	80	100	☐
GT-1170HDL	1220x9,0	372/8	80	100	☐