

Specyfikacje



Eaton C10G1

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 1 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder



General specifications

PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C10G1
EAN	5027590493383
UPC	051712754217
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	8.2 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269
MODEL CODE	CYLINDRICAL FUSE 10 x 38 1A GG 500V AC

Electrical data

AMPERAGE RATING	1 A
VOLTAGE RATING	500 V
VOLTAGE TYPE	AC
BREAKING CAPACITY	120 kA
CLASS	Class C gL/gG
FREQUENCY RATING - MAX	62 Hz

Compatible fuse holder

SUITABLE FOR	CHM Modular fuse holder
---------------------	-------------------------

Do pobrania

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf](#)

DEKLARACJE ZGODNOŚCI

[eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

Follow us on social media to get the latest product and support information.

