

# Specyfikacje



## Eaton ICS-R16D024B200

Eaton Distribution parts. Installation relay, 24 V DC, 2NO, 16A

### General specifications

<b>PRODUCT NAME</b>	Eaton Distribution parts
<b>CATALOG NUMBER</b>	ICS-R16D024B200
<b>EAN</b>	9010238030169
<b>PRODUCT LENGTH/DEPTH</b>	90 mm
<b>PRODUCT HEIGHT</b>	73 mm
<b>PRODUCT WIDTH</b>	17.5 mm
<b>PRODUCT WEIGHT</b>	0.097 kg
<b>COMPLIANCES</b>	RoHS conform
<b>MODEL CODE</b>	Z-R23/16-20

Zdjęcie jest reprezentatywne



**EATON**

Powering Business Worldwide

## Specyfikacje produktu

<b>AMPERAGE RATING</b>	16 A
<b>MOUNTING METHOD</b>	DIN rail
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF</b>	Does not apply, since the

## Do pobrania

<b>RYSUNKI</b>	<a href="#">eaton-dimensions-mas-z-r-ics.jpg</a>
<b>SCHEMATY POŁĄCZEŃ</b>	<a href="#">Z R 1TE</a>

<b>PROTECTION OF ASSEMBLIES</b>	entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	0.8 W
<b>CONTROL VOLTAGE 1 TYPE</b>	DC
<b>CONTROL VOLTAGE 1 - MAX</b>	26 V
<b>CONTROL VOLTAGE 1 - MIN</b>	21 V
<b>CONTROL VOLTAGE 2 - MAX</b>	0 V
<b>CONTROL VOLTAGE 2 - MIN</b>	0 V
<b>FREQUENCY CONTROL VOLTAGE 1 - MAX</b>	0 Hz
<b>FREQUENCY CONTROL VOLTAGE 1 - MIN</b>	0 Hz
<b>FREQUENCY CONTROL VOLTAGE 2 - MAX</b>	0 Hz
<b>FREQUENCY CONTROL VOLTAGE 2 - MIN</b>	0 Hz
<b>INCANDESCENT LAMP LOAD - MAX</b>	720 W
<b>LOAD FLUORESCENT LAMP - MAX</b>	303 VA

<b>LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX</b>	541 VA
<b>LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX</b>	271 VA
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	2
<b>CONTROL VOLTAGE 2 TYPE</b>	AC/DC
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	16 A
<b>SUPPLY VOLTAGE - MAX</b>	240 V
<b>SUPPLY VOLTAGE - MIN</b>	240 V
<b>SWITCHING CURRENT (COS PHI = 0.6) - MAX</b>	5 A
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	1
<b>BUILT-IN DEPTH</b>	60 mm
<b>VOLTAGE TYPE</b>	AC
<b>FUNCTIONS</b>	Mechanical

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATA:**



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Irelandia  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Wszelkie prawa zastrzeżone.