

ENSTO

PRODUCT SPECIFICATION

2020-02-24



6418677191930

Terminal block

KE64.3

Code	KE64.3
GTIN	6418677191930
Name	Terminal block Ensto Clampo Pro 1-pole, yellow/green, Al/Cu 35-240 mm ²
Description	Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm ² .
Vendor	Ensto Finland Oy



Technical specification

Others

ETIM Class: EC000897

Material

Housing: Polyamide

Colors

Color: Yellow-green

Certificates

Connector class: A
 Standards: EN 61238-1, UL 1059, EN 60947-7-2
 UL category: XCFR2
 UL File no.: E192532, E192532

US specific

Maximum voltage: 600 V

Dimensions

Conductor cross-section: 35-240
 Conductor size: 500-3/0
 Dimensions l x w x h: 130 x 37.5 x 67
 Net Weight: 0,249 kg
 Weight: 0,249 kg

Features

Mounting:	Screw
Number of poles:	1
Screw head:	Hexagon
Screw head size:	8 mm

Temperatures

Operating temperature:	$\leq 80\text{ }^{\circ}\text{C}$
------------------------	-----------------------------------

Electrical values

Nominal insulation voltage:	800 V
Pollution degree:	3

ETIM 7

Etim

Colour:	Green/yellow
Connectable conductor cross section fine-strand with cable end sleeve:	35 ... 185 mm ²
Connectable conductor cross section fine-strand without cable end sleeve:	15 ... 185 mm ²
Connectable conductor cross section multi-wired:	35 ... 240 mm ²
Connection position:	Sideways
Explosion-tested version 'Ex e':	False
Height at lowest possible mounting height:	67 mm
Inflammability class of insulation material acc. with UL94:	V2
Length:	130 mm
Material insulation body:	Thermoplastic
Mounting method:	Direct mounting
Number of clamp positions per level:	2
Number of levels:	1
Operation temperature:	-5 ... 80 °C
Rated voltage:	800 V
Type of electrical connection 1:	Screw connection
Type of electrical connection 2:	Screw connection
Width/grid dimension:	37,5 mm

Packaging

Default package

Unit:	PCE
Package size:	30
Depth:	383 mm
Width:	258 mm
Height:	131 mm

Weight:	19,086 kg
Volume:	12,944634 l