

ENSTO

PRODUCT SPECIFICATION

2020-02-24



6418677405112

Tension clamp

SO85



Code	SO85
GTIN	6418677405112
Name	Tension clamp Dia 6-14.9 mm (AAAC 25 - 150 mm ²)
Description	For dead-ending bare and covered conductors. The covered conductor has to be peeled before installing the clamp. The body is made of corrosion resistant aluminium alloy and the bolts are hot dip galvanized steel. Breaking load 35 kN. Suspension bolt 16 mm.

Vendor

Technical specification

Others

ETIM Class: EC003516

Certificates

Standards: IEC 61284

Features

Bolt: 2xM12
For conductor size: AAAC 25-150, PAS 35-150, ACSR 25-99

Mechanical

Breaking load: 35 kN
Max. continuous load: 20 kN
Tightening torque Nm: 55 Nm

Dimensions

Conductor diameter: 6 ... 14,9 mm
Suspension bolt: 16 mm
Weight: 0,74 kg

ETIM 7

Etim

Type of accessory: Other

Packaging

Pallet package

Unit: PCE
Package size: 800
Depth: 1210 mm
Width: 800 mm
Height: 1190 mm

Default package

Unit: PCE
Package size: 25
Depth: 405 mm
Width: 300 mm
Height: 255 mm
Volume: 30,9825 l